

SF100/101



Product Introduction

SF100/101 is an access control device produced by ZK Software, which is made from zinc alloy with elegant European design and professional surface treatment. This product adopts a lot of imported components, and strictly complies with the national security product standard. SF100/101 experiences strict degradation test before leaving factory. The product has three buttons including enrollment, delete and door bell. The operation with audio prompt is very convenient for customer. Dustproof cover and non-LCD designs always keep the device clean. The USB-Client communications interface eliminates the trouble of wiring. Built-in ID reader module offers customers different methods of use. SF100/101 is applicable for small office, house and some places with low-level security requirement.



Features:

- Easy installation, safe and reliable.
- Extreme Durability with Metallic Housing
- Anti-dust cover protects fingerprint sensor from ash, keeping clean.
- Simple and convenient operation method with full audio prompt.
- Supporting ID/Mifare/HID proximity card

Specification:

SF100

- Fingerprint Capacity: 200
- Card Capacity: 100
- Logs Capacity: 30,000
- Fingerprint sensor : ZK optical sensor
- Algorithm version : ZKFinger VX9.0
- Communication: RS232/485, USB client
- Access control : door sensor, alarm, lock, exit button, wired door bell
ID card is standard function
- Optional functions: Mifare/HID card
- Keypad: Register, delete, bell
- Power supply: DC12V 3A
- Identification time : $\leq 2S$
- FAR: $\leq 0.0001\%$
- FRR: $\leq 1\%$
- LED: Red, Green, Blue
- Operating Temperature : $0^{\circ}C-45^{\circ}C$
- Operating Humidity : 20%-80%
- Size: 120*120*35.1mm (W*H*D)

SF101

- Fingerprint Capacity: 200
- Card Capacity: 100
- Logs Capacity: 30,000
- Fingerprint sensor : ZK optical sensor
- Algorithm version : ZKFinger VX9.0
- Communication: RS232/485, USB client
- Access control : door sensor, alarm, lock, exit button, wired door bell
Wiegand output 26bit
ID card is standard function
- Optional functions: Mifare/HID card
- Keypad: Register, delete, bell
- Power supply: DC12V
- Identification time : $\leq 2S$
- FAR: $\leq 0.0001\%$
- FRR: $\leq 0.01\%$
- LED: Red, Green, Blue
- Operating Temperature : $0^{\circ}C-45^{\circ}C$
- Operating Humidity : 20%-80%
- Size: 120*120*35.1mm (W*H*D)



SMART TOUCH TECHNOLOGY SDN BHD

M'sia Office: 69A, Jalan Maju, Taman Tebrau Jaya, 80400 Johor Bahru, Johor.
Tel:07-333 4767 Fax:07-332 4768

S'pore Office: 116 Lavender Street, Pek Chuan Building #03-10, Singapore 338730.
Tel:65-6396 4767 Fax:65-6396 0539