



KR101E: 125KHz Proximity Card Reader

KR101M: 13.56MHz Mifare Card Reader

Feature:

- 125KHz Proximity /13.56MHz Mifare Card Reader
- Read Range: Up to 10CM(125KHz)/5CM(13.56MHz)
- 26/34bit Wiegand (default)
- Easy to install on Metal Door Frame or Mullion
- External LED Control
- External Buzzer Control
- Indoor / Outdoor Operation
- Solid Epoxy Potted
- Waterproof IP65
- Reverse Polarity Protection

Specification:

Model	KR101E	KR101M
Read Range	Up to 10CM	Up to 5CM
Reading Time (Card)	≤300ms	
Power / Current	DC 6-14V / Max.70mA	
Input Port	2ea (External LED Control, External Buzzer Control)	
Output Format	26bit Wiegand (default)	34bit Wiegand (default)
LED Indicator	2 Color LED Indicators(Red and Green)	
Beeper	Yes	
Operating Temperature	-10° to +70°C	
Operating Humidity	10% to 90% relative humidity non-condensing	
Color	Black	
Material	ABS+PC with texture	
Dimension (W x H x T)mm	77.5*42.8*16.5	
Weight	50g	
Index of Protection	IP65	

All design and specification declared are subject to change without notice in advance